


# SAFETYDATASHEET

## 1. Product and Company Identification

<b>Product identifier</b>	<b>W SERIES SOLVENT BASED STAINS – NON REGULATED</b>
<b>Other means of identification</b>	0113, W200, W201, W210, W215, W218, W231, W233, W234, W235, W236, W238, W239, W240, W241, W242, W243, W246, W247, W248, W249, W250, W251, W252, W253, W254, W255, W354, W355, WS200482, WS201020, WS201520, WS201811
<b>Recommended use</b>	Fast Dry Pigmented Wiping Stains
<b>Recommended restrictions</b>	None known.
<b>Manufacturer information</b>	John E. Goudey Manufacturing Limited 21 Primrose Avenue Toronto, ON M6H 3V1 CA Phone: (416)531-4669
<b>Supplier</b>	See above.
<b>CANUTEC</b>	(613) 996-6666

## 2. Hazards Identification

<b>Physical hazards</b>	Flammable liquids	<b>Label elements</b>	
<b>Health hazards</b>	Skin corrosion/irritation Serious eye damage/eye irritation Carcinogenicity Reproductive toxicity Specific target organ toxicity, single exposure Specific target organ toxicity, single exposure Specific target organ toxicity, repeated exposure Aspiration hazard	Category 4 Category 2 Category 2 Category 2 Category 2	
<b>Environmental hazards</b>	Not classified.		
<b>WHMIS 2015 defined hazards</b>	Not classified		
<b>Signal word</b>	Danger		
<b>Hazard statement</b>	Combustible liquid. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause respiratory irritation.		

Category 3 respiratory tract irritation  
Category 3 narcotic effects  
Category 1 (central nervous system)

None known.

Category 1

May cause drowsiness or dizziness. Causes damage to organs (central nervous system) exposure. May be fatal if swallowed and enters

**Precautionary statement** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Prevention** Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe mist or vapor. Use only outdoors or in a wellventilated area. Do not eat, drink or smoke when using this product.

---

**Response**

In case of fire: Use appropriate media to extinguish. IF ON SKIN: Wash with plenty of water. Specific treatment (see information on this label). If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned:

**Storage**

**Disposal**

**WHMIS 2015: Health Hazard(s) otherwise classified (HHNOC)**

**WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC) Hazard(s) not otherwise classified (HNOC) Supplemental information** Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting.

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

None known **not**

None known

None.

### 3. Composition/Information on Ingredients

### 4. First Aid Measures

CENTER or doctor/physician if you feel unwell.

#### Skin contact

attention and special treatment needed

#### Eye contact

IF ON SKIN: Wash with plenty of water. Specific treatment (see information on this label). If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

#### Ingestion

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

#### Most important symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects. Treat patient symptomatically.

#### Indication of immediate medical

#### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON

#### Mixture

Chemical name	Common name and synonyms	CAS number	%	
Benzene, ethyl-		100-41-4	1-5*	solvent
Carbon black		1333-86-4	0.1-1*	8052-
Ferric oxide		1309-37-1	1-5*	
Heavy aromatic solvent naphtha (petroleum)		64742-94-5	45-70*	Xylene 1330-
Hydrous magnesium silicate		14807-96-6	0.1-1*	All
Naphtha (petroleum), heavy alkylate		64741-65-7	0.1-1*	
Silica, amorphous, fumed, crystalline free		112945-52-5	0.1-1*	
Solvent naphtha (petroleum), medium aliphatic		64742-88-7	1-5*	

concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition comments** \*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.  
US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

**General information** IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

---

## 5. Fire Fighting Measures

---

**Suitable extinguishing media** **Unsuitable media** **Specific hazards arising from the chemical** **Special protective equipment and precautions for firefighters** **Fire-fighting equipment/instructions** **Specific methods** **General fire hazards** **Hazardous combustion products**

Water fog. Foam. Dry chemical powder. Carbon dioxide.

Do not use water jet as an extinguisher, as this will spread the fire. **extinguishing media**

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire. **and**

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

Combustible liquid.

May include and are not limited to: Oxides of carbon.

---

## 6. Accidental Release Measures

---

**Personal protective equipment and emergency procedures** **Methods and materials for containment and cleaning up** **Environmental precautions**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Never return spills to original containers for re-use. Clean surface thoroughly to remove residual contamination. Following product recovery, flush area with water. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.

Do not discharge into lakes, streams, ponds or public waters.

---

## 7. Handling and Storage

---

**Precautions for safe handling** **Conditions for safe storage including any incompatibilities**

Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear appropriate personal protective equipment. Do not breathe mist or vapor. Use only outdoors or in a well-ventilated area. Avoid contact with eyes, skin, and clothing. Pregnant or breastfeeding women must not handle this product. Avoid prolonged exposure. Use good industrial hygiene practices in handling this material. When using do not eat or drink.

Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children.

---

## 8. Exposure Controls/Personal Protection

---

**Occupational exposure limits**

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
	TW	543 mg/m3	125 ppm
	A		434 mg/m3
	TW		100 ppm
	A		Repirabl
			3.5 e. mg/m3
			5 mg/m3
Benzene, ethyl- (CAS 100-41-4)	STEL		3 e particles.
			2 mg/m3
Carbon black (CAS 1333-86-4)			3
Ferric oxide (CAS 1309-37-1)			1590
Hydrous magnesium silicate (CAS 14807-96-6)	TWA		<b>Type</b>
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)	TWA		mg/m3
<b>Canada. Alberta OELs (Occupational Health &amp; Safety Code, Schedule 1, Table 2)</b>	<b>TWA</b>	<b>Components</b>	<b>Value</b>
			<b>Form</b>

Stoddard solvent (CAS 8052-41-3)	TWA	400 ppm	572 mg/m3
			100 ppm
Xylene (CAS 1330-20-7)	STEL	651 mg/m3	150 ppm
	TWA	434 mg/m3	100 ppm

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Safety Regulation 296/97, as amended)			
Components	Type	Value	Form
Benzene, ethyl- (CAS 100-41-4)	TWA	20 ppm	
Carbon black (CAS 1333-86-4)	TWA	3 mg/m3	
Ferric oxide (CAS 1309-37-1)	STEL	10 mg/m3	Inhalable Fume.

	TWA	5 mg/m <sup>3</sup>	Fume.	fraction.
		5 mg/m <sup>3</sup>	Dust.	
		3 mg/m <sup>3</sup>	Respirable	
		10 mg/m <sup>3</sup>	Total dust.	
Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	TWA	200 mg/m <sup>3</sup>	Non-aerosol.	
Hydrous magnesium silicate (CAS 14807-96-6)	TWA	2 mg/m <sup>3</sup>	Respirable.	
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	TWA	200 mg/m <sup>3</sup>	Non-aerosol.	
Stoddard solvent (CAS 8052-41-3)	STEL	580 mg/m <sup>3</sup>		
	TWA	290 mg/m <sup>3</sup>		
	STEL	150 ppm		
Xylene (CAS 1330-20-7)	TWA	100 ppm		

#### Canada. Manitoba OELs (Reg. 217/2006, Th

		Type	Value	Form
Benzene, ethyl- (CAS 10041-4)	TWA TWA		20 ppm	Inhalable fraction.
Carbon black (CAS 133386-4)				
Ferric oxide (CAS 1309-37-1)	TWA		3 mg/m <sup>3</sup>	Respirable fraction.
Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	TWA		5 mg/m <sup>3</sup>	Non-aerosol.
			200 mg/m <sup>3</sup>	
Hydrous magnesium silicate (CAS 14807-96-6)	TWA			Respirable fraction.
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	TWA		2 mg/m <sup>3</sup>	Non-aerosol.
Stoddard solvent (CAS 8052-41-3)			200 mg/m <sup>3</sup>	
Xylene (CAS 1330-20-7)	TWA			
	STEL		100 ppm	
	TWA		150 ppm	
			100 ppm	

#### Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents

Components		Type	Value	Form
Benzene, ethyl- (CAS 10041-4)	TWA		20 ppm	Inhalable fraction.
Carbon black (CAS 133386-4)				Respirable fraction.
Ferric oxide (CAS 1309-37-1)	TWA		3 mg/m <sup>3</sup>	
Hydrous magnesium silicate (CAS 14807-96-6)	TWA		5 mg/m <sup>3</sup>	
	TWA		2 fibers/ml	

		2 mg/m3	Respirable fraction.
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)		525 mg/m3	
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	TWA	200 mg/m3	Non-aerosol.
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm	
Xylene (CAS 1330-20-7)	TWA	150 ppm	
	STEL TWA	100 ppm	
<b>Canada. Quebec OELs. (Ministry of Labor Regulation Respecting the Quality of the Work Environment) Form</b>			
<b>Components</b>	<b>Type</b>	<b>Enviro Value</b>	<b>Form</b>
Benzene, ethyl- (CAS 100-41-4)	STEL	543 mg/m3	
		125 ppm	
	TWA	434 mg/m3	
		100 ppm	
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3	
Ferric oxide (CAS 1309-37-1)	TWA	5 mg/m3	
	TWA	10 mg/m3	Dust and fume.
Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)		1590 mg/m3	Total dust.
		400 ppm	
Hydrous magnesium silicate (CAS 14807-96-6)	TWA	3 mg/m3	Respirable dust.
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)	TWA	1590 mg/m3	
		400 ppm	
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	TWA	1590 mg/m3	
		400 ppm	
Stoddard solvent (CAS 8052-41-3)	TWA	525 mg/m3	
		100 ppm	
Xylene (CAS 1330-20-7)	STEL	651 mg/m3	
		150 ppm	
	TWA	434 mg/m3	
		100 ppm	
<b>US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)</b>			
<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Benzene, ethyl- (CAS 100-41-4)	PEL	435 mg/m3	
		100 ppm	
Carbon black (CAS 1333-86-4)	PEL	3.5 mg/m3	
Ferric oxide (CAS 1309-37-1)	PEL	10 mg/m3	Fume.
<b>US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)</b>			
<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	PEL	400 mg/m3
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)	PEL	100 ppm 400 mg/m3
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	PEL	100 ppm 400 mg/m3
Stoddard solvent (CAS 8052-41-3)	PEL	100 ppm 2900 mg/m3
Xylene (CAS 1330-20-7)	PEL	500 ppm 435 mg/m3 100 ppm

**US. OSHA Table Z-3 (29 CFR 1910.1000)  
Components**

<u>Components</u>	<u>Type</u>	<u>Value</u>	<u>Form</u>
Ferric oxide (CAS 1309-37-1)	TWA	5 mg/m3	Respirable
		15 mg/m3	Total dust
		50 mppcf	Total dust
		15 mppcf	Respirable
Hydrous magnesium silicate (CAS 14807-96-6)	TWA	0.1 mg/m3	Respirable
	TWA	20 mppcf	
Silica, amorphous, fumed, crystalline free (CAS 112945-52-5)		2.4 mppcf 0.8 mg/m3	Respirable.
		20 mppcf	

**US. ACGIH Threshold Limit Values  
Components**

<u>Components</u>	<u>Type</u>	<u>Value</u>	<u>Form</u>
Benzene, ethyl- (CAS 10041-4)	TWA TWA	20 ppm	Inhalable fraction.
Carbon black (CAS 133386-4)			
Ferric oxide (CAS 1309-37-1)	TWA	3 mg/m3	Respirable fraction.
Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	TWA	5 mg/m3	Non-aerosol.
Hydrous magnesium silicate (CAS 14807-96-6)	TWA	200 mg/m3	Respirable fraction.
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	TWA	2 mg/m3	Non-aerosol.
Stoddard solvent (CAS 8052-41-3)	TWA	200 mg/m3	
Xylene (CAS 1330-20-7)	STEL	100 ppm	
	TWA	150 ppm	
		100 ppm	

**US. NIOSH: Pocket Guide to Chemical Hazards  
Components**

<u>Components</u>	<u>Type</u>	<u>Value</u>	<u>Form</u>
-------------------	-------------	--------------	-------------



Benzene, ethyl- (CAS 100-41-4)	STEL	545 mg/m3
		125 ppm
	TWA	435 mg/m3
		100 ppm
Carbon black (CAS 1333-86-4)	TWA	0.1 mg/m3

<b>US. NIOSH: Pocket Guide to Chemical Haz Components</b>	<b>ards Type</b>	<b>Value</b>	<b>Form</b>
Ferric oxide (CAS 1309-37-1)	TWA	5 mg/m3	Dust and fume.
Hydrous magnesium silicate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable.
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)	TWA	400 mg/m3	
		100 ppm	
Silica, amorphous, fumed, crystalline free (CAS 112945-52-5)	TWA	6 mg/m3	
Stoddard solvent (CAS 8052-41-3)	Ceiling	1800 mg/m3	
	TWA	350 mg/m3	
Xylene (CAS 1330-20-7)	STEL TWA	655 mg/m3	
		150 ppm	
		435 mg/m3	
		100 ppm	

#### Biological limit values

##### ACGIH Biological Exposure Indices

<b>Components</b>	<b>Value</b>	<b>Determinant</b>	<b>Specimen Sampling Time</b>
Benzene, ethyl- (CAS 100-41-4)	0.15 g/g	Sum of Creatinine * mandelic acid in urine and phenylglyoxylic acid	
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric Creatinine * acids in urine	

\* - For sampling details, please see the source document.

#### Exposure guidelines

##### Canada - Alberta OELs: Skin designation

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	Can be absorbed through the skin.
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	Can be absorbed through the skin.

##### Canada - British Columbia OELs: Skin designation

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	Can be absorbed through the skin.
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	

##### Canada - Manitoba OELs: Skin designation

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	

##### Canada - Ontario OELs: Skin designation

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	
---	--

Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)

**Canada - Saskatchewan OELs: Skin designation** Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)

Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)

**US ACGIH Threshold Limit Values: Skin designation**

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)

Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)

Can be absorbed through the skin.

Can be absorbed through the skin.

Can be absorbed through the skin.

Can be absorbed through the skin.

Can be absorbed through the skin.

Can be absorbed through the skin.

Can be absorbed through the skin.

Can be absorbed through the skin.

Can be absorbed through the skin.

**Appropriate engineering controls** Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates **controls** should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. **Individual protection measures, such as personal protective equipment**

**Upper/lower flammability or explosive limits**

**Eye/face protection** As required by employer code.

**Skin protection** Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.

**Hand protection** Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2). Not applicable.

**Other**

**Respiratory protection**

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. When using do not eat or drink.

**Thermal hazards**

**General hygiene considerations**

**9. Physical and Chemical Properties**

**Appearance** Liquid

**Physical state** Liquid.

**Form Color** Colored

**Odor Odor** Aromatic.

**threshold pH** Not available.

**Melting point/freezing point** Not available.

**Initial boiling point and boiling range** < 32 °F (< 0 °C)

**Pour point** 181.4 - 354.2 °F (83 - 179 °C)

**Specific gravity**

**Partition coefficient (n-octanol/water)** Not available.  
0.95 - 1.05

**Flash point** Not available.

**Evaporation rate**

**Flammability (solid, gas)** Wear safety glasses with side shields (or goggles). 149.0 °F (65.0 °C) TCC

Not available.

Not applicable.

---

Impervious gloves. Confirm with reputable supplier first.

**Flammability limit - lower (%)**

**Flammability limit - upper (%)**

Not available.

**Explosive limit - lower (%)** Not available. **Explosive**

**limit - upper (%) Vapor pressure Vapor density**

**Relative density Solubility(ies)** Not available. **Auto-ignition temperature** Not available.

**Decomposition temperature** 5.5 mm Hg @20C

**Viscosity** N

**Other information Explosive properties Oxidizing** o

**properties t**

**VOC (Weight %)** a

v

a

i

---

## 10. Stability and Reactivity

---

### Reactivity

This product may react with strong oxidizing agents.

---

1 a

b o l n e d  
 .  
 N o o n t a a Z v a a h i n l s  
 # a 2 b  
 l N e o  
 . t  
 N e e x  
 g p l l i o g s i i  
 b v l e  
 . e  
 N  
 Not available. o  
 N  
 t  
 o  
 a x  
 v  
 i  
 a i d  
 l a i b l z e. i  
 1 n  
 6 g s .  
 e 716 - 788 g/l c

---

**Incompatible materials**  
**Hazardous decomposition products**

Material is stable under normal conditions.

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Do not mix with other chemicals.

Strong acids. Strong oxidizing agents. Halogens. Aluminum. Strong bases. May include and are not limited to: Oxides of carbon.

**Routes of exposure**

**Information on likely routes of**

**Ingestion**

**Inhalation**

**Skin contact**

**Eye contact**

**Symptoms related to the physical, chemical and toxicological characteristics**

Hazardous polymerization does not occur.

**11. Toxicological Information**

Eye, Skin contact, Inhalation, Ingestion. **posure**

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. May cause stomach distress, nausea or vomiting.

May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. May cause irritation to the respiratory system.

Causes skin irritation.

Causes serious eye irritation.

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.

**Information on toxicological effects**

**Acute toxicity**

**Components**

Benzene, ethyl- (CAS 100-41-4)

**Acute**

*Dermal* LD50

Ferric oxide (CAS 1309-37-1) **Acute**

*Dermal* LD50

*Inhalation*

LC50

May be fatal if swallowed and enters airways. Narcotic effects. May cause respiratory irritation.

*Inhalation*  
LC50

*Oral*  
LD50

**Species**

Rabbit

**Test Results**

17800 mg/kg, HSDB  
 15380 mg/kg, CCOHS: Cheminfo  
 17.8 ml/kg, 24 Hours, ECHA

Carbon black (CAS 1333-86-4)

**Acute**

*Dermal* LD50

*Inhalation*  
LC50

*Oral*  
LD50

Mouse

Rat

Rat

> 8000 ppm, 20 Minutes, ECHA  
 4000 ppm, 4 Hours, CCOHS: Cheminfo  
 5460 mg/kg, HSDB  
 3500 mg/kg, Sigma Aldrich  
 5.5 g/kg, ECHA/HSDB

> 8000 mg/kg, ECHA/HSDB

Rabbit > 3000 mg/kg

Not available

Rat > 15400 mg/kg  
>

1 \_\_\_\_\_  
Not available 0







**Components****Species Test Results***Oral*

LD50 Rat &gt; 10000 mg/kg, ECHA

&gt; 5000 mg/kg, ECHA Heavy

aromatic solvent naphtha (petroleum) (CAS 64742-94-5)

**Acute***Dermal*

LD50 Rabbit &gt; 6000 mg/kg, 24 Hours

&gt; 4000 mg/kg, 24 Hours

&gt; 2000 mg/kg, 24 Hours, ECHA

Rat

&gt; 2000 mg/kg, 24 Hours, ECHA

*Inhalation*

LC50 Rat &gt; 7.5 mg/L, 6 Hours, ECHA

&gt; 4.3 mg/L, 4 Hours, ECHA

> 0.1 mg/L, 8 Hours, ECHA *Oral*

LD50 Rat

&gt; 5000 mg/kg

&gt; 2000 mg/kg, ECHA

7050 mg/kg, HMIRC

5800 mg/kg, ECHA

4820 mg/kg, ECHA Hydrus

magnesium silicate (CAS 14807-96-6)

**Acute***Dermal*

LD50 Rat

&gt; 2000 mg/kg, ECHA

*Inhalation* > 2.1 mg/L, 4 h, ECHA LC50 Rat*Oral*

&gt; 5000 mg/kg, ECHA

LD50 Rat

Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)

**Acute***Dermal*

LD50 Rabbit &gt; 6000 mg/kg, 24 Hours, ECHA

> 3750 mg/kg, 24 Hours,  
ECHA> 3000 mg/kg, 24 Hours,  
ECHA

&gt; 2000 mg/kg, ECHA

**Components**

**Species Test Results**

> 2000 mg/kg, 24 Hours,  
ECHA

> 1900 mg/kg, 24 Hours,

ECHA *Inhalation*

LC50 Rat > 8530 mg/m3, 4 Hours, ECHA > 7970 mg/m3, 4 Hours, ECHA

> 7630 mg/m3, 4 Hours, ECHA

> 7300 mg/m3, 4 Hours, ECHA

> 5830 mg/m3, 4 Hours, ECHA

> 5740 mg/m3, 4 Hours, ECHA

> 5610 mg/m3, 4 Hours, ECHA

> 5470 mg/m3, 4 Hours, ECHA

> 5300 mg/m3, 4 Hours, ECHA

> 5280 mg/m3, 4 Hours, ECHA

> 5260 mg/m3, 4 Hours, ECHA

> 5250 mg/m3, 4 Hours, ECHA

> 5240 mg/m3, 4 Hours, ECHA

> 5220 mg/m3, 4 Hours, ECHA

Silica, amorphous, fumed, crystalline free (CAS 112945-52-5)

**Acute**

*Dermal*

LD50

Rabbit

*Inhalation* LC50 Rat

**Components**

**Species Test Results**

>  
5570

> 5200 mg/m3, 4 Hours, ECHA

> 5170 mg/m3, 4 Hours, ECHA

> 5160 mg/m3, 4 Hours, ECHA

> 5100 mg/m3, 4 Hours, ECHA

> 5080 mg/m3, 4 Hours, ECHA

> 5050 mg/m3, 4 Hours, ECHA

Oral  
LD50

mg/kg, ECHA                      Rat  
   > 4800 mg/kg, ECHA   > 5200 mg/kg, ECHA  
> 4500 mg/kg, ECHA   > 5000 mg/kg, ECHA

> 5040 mg/m3, 4 Hours, ECHA  
> 5020 mg/m3, 4 Hours, ECHA  
> 5000 mg/m3, 4 Hours, ECHA  
> 4980 mg/m3, 4 Hours, ECHA  
> 4970 mg/m3, 4 Hours, ECHA  
> 4420 mg/m3, 4 Hours, ECHA  
> 5.4 mg/L, 4 Hours, ECHA  
> 5.1 mg/L, 4 Hours, ECHA  
> 5.1 mg/L, 4 Hours, ECHA  
> 5 mg/L, 4 Hours, ECHA  
> 5 mg/L, 4 Hours, ECHA  
73680 mg/L, 4 Hours, HSDB  
>= 5060 mg/m3, 4 Hours, ECHA  
61 mg/L, 4 Hours, HSDB  
> 7000 mg/kg, ECHA  
> 6000 mg/kg, ECHA  
> 25 ml/kg, HSDB  
14063 mg/kg, ECHA

**Components**

**Species Test Results**

6620 mg/kg, ECHA

5800 mg/kg, ECHA

5390 mg/kg, ECHA

4820 mg/kg, ECHA

> 5000 mg/kg, 24 Hours,  
ECHA

> 2000 mg/kg, 24 Hours

> 58.8 mg/L, 4 Hours,  
ECHA

> 2.1 mg/L, 4 Hours, ECHA

> 0.7 mg/L, 4 Hours, ECHA

> 0.1 mg/L, 4 Hours, ECHA

*Oral*

LD50

Mouse

> 15000 mg/kg, HSDB

> 3160 mg/kg

Rat

> 10000 mg/kg, ECHA

> 5000 mg/kg, ECHA

> 3300 mg/kg

3160 mg/kg, LOLI

Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)

**Acute Dermal**

LD50

Rabbit

> 4000 mg/kg, 24 Hours

> 2000 mg/kg

> 2000 mg/kg, 24 Hours

3000 mg/kg, NIOSH

*Inhalation*

LC50

Cat

> 6.4 mg/L, 6 Hours

Rat

> 7.5 mg/L, 6 Hours

> 6 mg/L, 4 Hours, ECHA

**Components**

**Species Test Results**

			> 5.7 mg/L, 4 Hours, ECHA
			> 5.3 mg/L, 4 Hours, ECHA
			> 5.3 mg/L, 4 Hours, ECHA
			> 5.2 mg/L, 4 Hours, ECHA
			> 4.6 mg/L, 4 Hours, ECHA
			> 4.5 mg/L, 4 Hours, ECHA
			> 4.3 mg/L, 4 Hours
			> 0.1 mg/L, 8 Hours
			5.3 mg/l/4h, NIOSH
<i>Oral</i>			
LD50	Rat		> 20000 mg/kg
			> 5000 mg/kg, NIOSH
			> 25 ml/kg
Stoddard solvent (CAS 8052-41-3)			
<b>Acute</b>			
<i>Dermal</i>			
LD50	Rabbit		> 3000 mg/kg
<i>Inhalation</i>			
LC50	Rat		> 5500 mg/m3
<i>Oral</i>			
LD50	Rat		> 5000 mg/kg
Xylene (CAS 1330-20-7)			
<b>Acute</b>			
<i>Dermal</i>			
LD50	Rabbit		> 5000 ml/kg, 4 Hours, ECHA
			> 43 g/kg, HSDB
			12126 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>			
LC50	Mouse		3907 mg/L, 6 Hours, HSDB
			3907 ppm, 6 Hours, HSDB
	Rat		6700 ppm, 4 Hours, ECHA

**Components**

**Species Test Results**

*Oral*  
LD50

**Skin corrosion/irritation**

**Exposure minutes**

**Erythema value**

**Oedema value**

**Serious eye damage/eye  
irritation**

**Corneal opacity value**

**Iris lesion value**

**Conjunctival reddening value Conjunctival oedema value**

**Recover days**

**Respiratory or skin sensitization**

**Respiratory sensitization**

**Components**

**Species Test Results**

**Skin sensitization**

HA/HSDB

**Mutagenicity**

6247 ppm, 4 Hours, ECHA

**Carcinogenicity**

**ACGIH Carcinogens**

5922 ppm, 4 Hours, ECHA

5627 mg/kg, ECHA/HSDB

6

5

8

0

p

p

m

Mouse

,

4

H

o

u

Rat

r s

Causes skin irritation. ,  
E Not available.

C

Not available.

H

Not available.

A

5251 mg/kg, ECHA

> 4000 mg/kg, ECHA 6670  
mg/kg, HSDB

4300 mg/kg, ECHA/HSDB

3523 mg/kg

10 ml/kg, ECHA

Causes serious eye irritation.

6 3

Not available.

5

Not available.

0

Not available.

p p

m

Not available.

,

Not available.

4

H

o

Not a respiratory sensitizer. u

This product is not expected to cause skin sensitization. r

No data available to indicate product or any components pres<sup>S</sup>ent at greater than 0.1%  
are mutagenic or genotoxic. '

E

Suspected of causing cancer. See below. C



Benzene, ethyl- (CAS 100-41-4)

Carbon black (CAS 1333-86-4)

Crystalline silica (CAS 14808-60-7) Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)

Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)

**Canada - Alberta OELs: Carcinogen category**

Crystalline silica (CAS 14808-60-7)

**Canada - Manitoba OELs: carcinogenicity**

CARBON BLACK, INHALABLE FRACTION (CAS 1333-86-4)

ETHYL BENZENE (CAS 100-41-4)

KEROSENE (NON-AEROSOL), AS TOTAL HYDROCARBON VAPOR (CAS 64742-88-7)  
KEROSENE (NON-AEROSOL), AS TOTAL

HYDROCARBON VAPOR (CAS 64742-94-5) SILICA, CRYSTALLINE-.ALPHA.-QUARTZ, RESPIRABLE FRACTION (CAS 14808-60-7) **Canada -**

**Quebec OELs: Carcinogen category**

Crystalline silica (CAS 14808-60-7)

**IARC Monographs. Overall Evaluation of Carcinogenicity**

Benzene, ethyl- (CAS 100-41-4) Carbon black (CAS 1333-86-4) Crystalline silica (CAS 14808-60-7) A3 Confirmed animal carcinogen with unknown relevance to humans.

A3 Confirmed animal carcinogen with unknown relevance to humans.

A2 Suspected human carcinogen.

A3 Confirmed animal carcinogen with unknown relevance to humans.

A3 Confirmed animal carcinogen with unknown relevance to humans.

Suspected human carcinogen.

Confirmed animal carcinogen with unknown relevance to humans.

Confirmed animal carcinogen with unknown relevance to humans.

Confirmed animal carcinogen with unknown relevance to humans.

Confirmed animal carcinogen with unknown relevance to humans.

Suspected human carcinogen.

Suspected carcinogenic effect in humans.

Volume 77 - 2B Possibly carcinogenic to humans.

Volume 65, Volume 93 - 2B Possibly carcinogenic to humans. Volume 68, Volume 100C 1 Carcinogenic to humans.

Ferric oxide (CAS 1309-37-1)

Volume 1, Supplement 7 - 3 Not classifiable as to carcinogenicity to humans.

Hydrous magnesium silicate (CAS 14807-96-6)

Volume 42, Supplement 7, Volume 93 - 3 Not classifiable as to carcinogenicity to humans.

Silica, amorphous, fumed, crystalline free (CAS 112945-52-5)

Volume 93 - 2B Possibly carcinogenic to humans.

Stoddard solvent (CAS 8052-41-3)

Volume 68 - 3 Not classifiable as to carcinogenicity to humans.

Xylene (CAS 1330-20-7)

Volume 47 - 3 Not classifiable as to carcinogenicity to humans.

Volume 47, Volume 71 - 3 Not classifiable as to carcinogenicity to humans.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Benzene, ethyl- (CAS 100-41-4)

Carbon black (CAS 1333-86-4)

Crystalline silica (CAS 14808-60-7)

**US NTP Report on Carcinogens: Known carcinogen**

Crystalline silica (CAS 14808-60-7) Known To Be Human Carcinogen. **US. OSHA Specifically**

**Regulated Substances (29 CFR 1910.1001-1050)**

Crystalline silica (CAS 14808-60-7)

Cancer

**Reproductive toxicity**

Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging fertility or the unborn child.

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)

Algae

IC50

Alg

Algae

IC50

Algae

**Aquatic**

Crustacea	EC50	Daphnia	Crustacea	EC50	W
<b>Aquatic</b>			Fish	LC50	Ra
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.5 mg/L, 72 Hours		(O
			0.95 mg/L, 48 Hours		
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)			8.8 mg/L, 96 hours		

#28351

Page: 21 of 27

Issue date 27-June-2018

**Teratogenicity**

Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Xylene is considered fetotoxic in humans, based on observations of reduced fetal weight, delayed ossification and persistent behavioural effects in animal studies in the absence of maternal toxicity.

**Specific target organ toxicity - May cause respiratory irritation. May cause drowsiness and dizziness. single exposure**

**Specific target organ toxicity - Causes damage to organs (central nervous system) through prolonged or repeated exposure.**

**repeated exposure Aspiration hazard** May be fatal if swallowed and enters airways.

**Chronic effects**

Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. Significant lung effects have been observed in animals following exposure to airborne concentrations of Carbon Black of less than 100 mg/m3.

**12. Ecological Information**

Ecotoxicity Ecotoxicological data	See below Components	Species	Test Results
Benzene, ethyl- (CAS 100-41-4) IC50		Algae	4.6 mg/L, 72 Hours
Algae			
Crustacea	EC50	Daphnia	2.1 mg/L, 48 Hours
<b>Aquatic</b>	EC50	Water flea (Daphnia magna)	1.37 - 4.4 mg/L, 48 hours
Crustacea		Fish LC50	Fathead minnow (Pimephales promelas) 7.5 - 11 mg/L, 96 hours

8.8 mg/L, 96 hours

30000 mg/L, 72 Hours

LC50

Fish  
(Oncorhynchus mykiss)

2.7 - 5.1 mg/L, 48 hours

**Components**

**Species**

Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)

Xylene (CAS 1330-20-7)

Crustacea

EC50

Daphnia

**Aquatic**

**Aquatic**

EC50

Water flea (Daphnia pulex)

Fish

LC50

Bluegill

Crustacea

(Lepomis macrochirus)

8.8 mg/L, 96 hours

2.7 - 5.1 mg/L, 48 hours

8.8 mg/L, 96 hours

8.8 mg/L, 96 hours

8.8 mg/L, 96 hours

**Test Results**

100 mg/L, 48 Hours

7.711 - 9.591 mg/L, 96 hours

**Persistence and degradability**  
**Bioaccumulative potential**

No data is available on the degradability of this product.

**Mobility in soil**

No data available.

**Mobility in general**

Not available.

**Other adverse effects**

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation)

---

### 13. Disposal Considerations

---

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations. The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Hazardous waste code</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Waste from residues / unused products</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
<b>Contaminated packaging</b>	

---

### 14. Transport Information

---

<b>Transport of Dangerous Goods (TDG) Proof of Classification</b>	Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.
---	--

**General**

Canada: Marine Pollutants Exemption. 1.45.1. : Part 3, Documentation, and Part 4, Dangerous Goods Safety Marks, do not apply to substances that are classified as marine pollutants in accordance with section 2.43 of Part 2, Classification, if they are in transport solely on land by road vehicle or railway vehicle. However, substances may be identified as marine pollutants on a shipping document and the required dangerous goods safety marks may be displayed when they are in transport by road or railway vehicle. (SOR/2008-34, s. 23)

US: DOT - 49 CFR 173.150 (f) - Combustible Liquid Exemption

CFR 171.4: The requirements of this subchapter specific to marine pollutants does not apply to non-bulk packagings transported by motor vehicle, rail car or aircraft, except when all or part of the transportation is by vessel.

#28351

Page: 22 of 27

Issue date 27-June-2018

**U.S. Department of Transportation (DOT)** Not regulated as dangerous goods.

**Transportation of Dangerous Goods (TDG - Canada)** Not regulated as dangerous goods.

---

### **15. Regulatory Information**

**Canadian federal regulations** contains all the information required in accordance with the hazard criteria of the HPR and the SDS required by the HPR. **Canada CEPA Schedule I: Listed substance** 2-Butanone, oxime (CAS 96-29-7) Listed. Ferric oxide (CAS 1309-37-1) Listed.

Hydrous magnesium silicate (CAS 14807-96-6) Listed. **Canada**

**DSL Challenge Substances: Listed substance**

2-Butanone, oxime (CAS 96-29-7) Listed. Carbon black (CAS 1333-86-4)

Listed. Crystalline silica (CAS 14808-60-7) Listed.

---

**Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number**

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	1 TONNES
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)	
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	1 TONNES
Stoddard solvent (CAS 8052-41-3)	1 TONNES
Xylene (CAS 1330-20-7)	1 TONNES

**Canada Priority Substances List (Second List): Listed substance**

Ferric oxide (CAS 1309-37-1) Listed.

Hydrous magnesium silicate (CAS 14807-96-6) Listed. **Export Control**

**List (CEPA 1999, Schedule 3)**

Not listed.

**Greenhouse Gases**

Not listed.

**Precursor Control Regulations** Not regulated.

**WHMIS 2015 Exemptions**

Not applicable

**US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Benzene, ethyl- (CAS 100-41-4) Listed. Manganese Oxide (CAS 1317-34-6)  
Listed. Xylene (CAS 1330-20-7) Listed.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)** Crystalline silica (CAS 14808-60-7) Cancer

lung effects immune system effects kidney effects

Benzene, ethyl- (CAS 100-41-4)

Listed. **Superfund Amendments and Reauthorization Act of**

**1986** Carbon black (CAS 1333-86-4) Listed. **(SARA)** Ferric oxide (CAS 1309-37-1) Listed.

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-Listed. 94-5)

Hydrous magnesium silicate (CAS 14807-96-6) Listed.

Manganese Oxide (CAS 1317-34-6) Listed. Naphtha (petroleum), heavy alkylate (CAS 64741-65-7) Listed. Silica, amorphous, fumed, crystalline free (CAS 112945- Listed. 52-5)

#28351

Page: 23 of 27

Issue date 27-June-2018

**Hazard categories** Immediate Hazard - Yes  
Delayed Hazard - Yes Fire Hazard - Yes  
Pressure Hazard - No  
Reactivity Hazard - No  
No

**SARA 302**

No

**Extremely hazardous substance**

**SARA**

**311/312**

**Hazardous**

**chemical**

%

**SARA 313 (TRI CAS by reporting) number wt.**

**Chemical name**

100-41- 1-

Benzene, 4 5\* ethyl- 1330- 10Xylene 20-7 30\*

**Other federal regulations**

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Benzene, ethyl- (CAS 100-41-4)  
Manganese Oxide (CAS 1317-34-6)  
Xylene (CAS 1330-20-7)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)** Not regulated.

**US state regulations**

**US - California Hazardous Substances (Director's): Listed substance**



Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Listed.  
Stoddard solvent (CAS 8052-41-3) Listed.  
Xylene (CAS 1330-20-7) Listed.

**US - Illinois Chemical Safety Act: Listed substance**

Benzene, ethyl- (CAS 100-41-4)  
Manganese Oxide (CAS 1317-34-6)  
Xylene (CAS 1330-20-7)

**US - Louisiana Spill Reporting: Listed substance**

Benzene, ethyl- (CAS 100-41-4) Listed.  
Manganese Oxide (CAS 1317-34-6) Listed.  
Xylene (CAS 1330-20-7) Listed.

**US - Michigan Critical Materials Register: Parameter number**

Xylene (CAS 1330-20-7) XYLENE (ALL ISOMERS)

**US - Minnesota Haz Subs: Listed substance**

2-Butanone, oxime (CAS 96-29-7) Listed. Benzene, ethyl- (CAS 100-41-4) Listed. Carbon black (CAS 1333-86-4) Listed. Crystalline silica (CAS 14808-60-7) Listed. Ferric oxide (CAS 1309-37-1) Listed.  
Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5) Listed.  
Hydrous magnesium silicate (CAS 14807-96-6) Listed. Manganese Oxide (CAS 1317-34-6) Listed.  
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7) Listed. Silica, amorphous, fumed, crystalline free (CAS 11294552-5) Listed.  
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Listed.  
Stoddard solvent (CAS 8052-41-3) Listed. Xylene (CAS 1330-20-7) Listed.

**US - New Jersey RTK - Substances: Listed substance**

Benzene, ethyl- (CAS 100-41-4)  
Carbon black (CAS 1333-86-4)  
Crystalline silica (CAS 14808-60-7)  
Ferric oxide (CAS 1309-37-1)  
Hydrous magnesium silicate (CAS 14807-96-6)  
Manganese Oxide (CAS 1317-34-6)  
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)  
Stoddard solvent (CAS 8052-41-3)  
Xylene (CAS 1330-20-7)

**US - North Carolina Toxic Air Pollutants: Listed substance**

Manganese Oxide (CAS 1317-34-6)  
Xylene (CAS 1330-20-7)

**US - Texas Effects Screening Levels: Listed substance**

2-Butanone, oxime (CAS 96-29-7) Listed. Benzene, ethyl- (CAS 100-41-4) Listed. Carbon black (CAS 1333-86-4) Listed. Crystalline silica (CAS 14808-60-7) Listed. Ferric oxide (CAS 1309-37-1) Listed.  
Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5) Listed.  
Hydrous magnesium silicate (CAS 14807-96-6) Listed. Manganese Oxide (CAS 1317-34-6) Listed.  
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7) Listed. Silica, amorphous, fumed, crystalline free (CAS 11294552-5) Listed.  
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Listed.  
Stoddard solvent (CAS 8052-41-3) Listed. Xylene (CAS 1330-20-7) Listed.

**US - Washington Chemical of High Concern to Children: Listed substance**

Benzene, ethyl- (CAS 100-41-4)



**US. Massachusetts RTK - Substance List**

- Benzene, ethyl- (CAS 100-41-4)
- Carbon black (CAS 1333-86-4)
- Crystalline silica (CAS 14808-60-7)
- Ferric oxide (CAS 1309-37-1)
- Hydrous magnesium silicate (CAS 14807-96-6)
- Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)
- Silica, amorphous, fumed, crystalline free (CAS 112945-52-5)
- Stoddard solvent (CAS 8052-41-3)
- Xylene (CAS 1330-20-7)

**US. New Jersey Worker and Community Right-to-Know Act**

- Benzene, ethyl- (CAS 100-41-4)
- Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)
- Manganese Oxide (CAS 1317-34-6)
- Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Xylene (CAS 1330-20-7)

**US. Pennsylvania Worker and Community Right-to-Know Law**

- Benzene, ethyl- (CAS 100-41-4)
- Carbon black (CAS 1333-86-4)
- Crystalline silica (CAS 14808-60-7)
- Ferric oxide (CAS 1309-37-1)
- Hydrous magnesium silicate (CAS 14807-96-6)
- Manganese Oxide (CAS 1317-34-6)
- Silica, amorphous, fumed, crystalline free (CAS 112945-52-5) Stoddard solvent (CAS 8052-41-3)
- Xylene (CAS 1330-20-7)

**US. Rhode Island RTK**

- Benzene, ethyl- (CAS 100-41-4)
- Carbon black (CAS 1333-86-4)
- Crystalline silica (CAS 14808-60-7)
- Ferric oxide (CAS 1309-37-1)
- Hydrous magnesium silicate (CAS 14807-96-6)
- Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)
- Stoddard solvent (CAS 8052-41-3)
- Xylene (CAS 1330-20-7)

**US. California Proposition 65**

**WARNING:** This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

- Benzene, ethyl- (CAS 100-41-4) Listed: June 11, 2004
- Carbon black (CAS 1333-86-4) Listed: February 21, 2003
- Crystalline silica (CAS 14808-607) Listed: October 1, 1988

**Inventory status**


Country(s) or region	Inventory name	On inventory	Canada	Domestic Substances List (DSL)	(yes/no)*	
Canada	Non-Domestic Substances List (NDSL)					Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory					No
						Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

## 16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	* 2
FLAMMABILITY	2
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X



**Disclaimer**

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

**Issue date**

27-June-2018

**Version #**

03

**Effective date**

27-June-2018

**Prepared by**

Dell Tech Laboratories, Ltd. Phone: (519) 858-5021

**Other information**

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.