SAFETYDATASHEET



1. Product and Company Identification

Product identifier

Synonyms

D500 Series NGR Stains

Other means of identification

D501, D502, D503, D504, D506, D507, D521, D529, D533, D534, D535, D536, D537,

DS504, DS521, DS537

Recommended use Non Grain Raising Stain

None known. Recommended restrictions

John E. Goudey Manufacturing Limited **Manufacturer information**

> 21 Primrose Avenue Toronto, ON M6H 3V1 CA Phone: (416)531-4669

Supplier See above. **CANUTEC** (613) 996-6666

2. Hazards Identification

Physical hazards Acute toxicity, oral Category 3

Health hazards Acute toxicity, inhalation Category 3

> Reproductive toxicity Category 1B

Specific target organ toxicity, single exposure Category 1

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated Category 1

Environmental hazards

WHMIS 2015 defined hazards

Label elements Not classified.

Not classified

exposure

Signal word

Hazard statement

Precautionary statement

Prevention



Danger

Highly flammable liquid and vapor. Toxic if swallowed. Toxic if inhaled. May damage fertility or the unborn child. May cause drowsiness or dizziness. Causes damage to organs.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray. Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood.

Storage

Disposal

Response

In case of fire: Use appropriate media to extinguish. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Specific treatment (see information on this label). Rinse mouth. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF exposed or concerned: Get medical advice/attention.

2015: Health Hazard(s) not Store in a well-ventilated place. Keep container tightly closed. Keep cool.

WHMIS

Store locked up.

otherwise classified Flammable liquids Category 2

#28042 Page: 1 of 14 Issue date 09-July-2018 WHMIS 2015: Physical

Hazard(s) not otherwise

classified (PHNOC) Hazard(s) otherwiseNone known. not

classified (HNOC)

1% of the mixture consists of component(s) of unknown acute inhalation toxicity.

Supplemental information

3. Composition/Information on Ingredients

Dispose of contents/container in

accordance with

local/regional/national/international regulations.

None known

None known

(HHNOC)

Chemical name	Common name and synonyms	CAS number	%
4-Heptanone, 2,6-dimethyl-		108-83-8	1-5*
Amines, C10-14-branched And		84961-40-0	1-5*
Linear Alkyl,			
Bis[2,4-dihydro-4-[(2-hydroxy-5-nitr			
ophenyl)azo]-5-methyl-2-phenyl-3h-			
pyrazol-3-onato(2-)]chromate(1-)			
(1:1)			
Methanol		67-56-1	80-100*

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments

US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a

trade secret.

4. First Aid Measures

Inhalation	IF INHALED:	Remove	person to	fresh air	and keep	comfortable	for breathing	. Call a F	POISON	
	0 = 1 · = = =									

CENTER or doctor/physician if you feel unwell. Specific treatment (see information on this label).

Skin contact IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical Eye contact

attention if irritation persists.

Ingestion IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Specific treatment

(see information on this label). Rinse mouth.

Most important symptoms/effects, acute and

delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes. Exposed individuals may experience eye tearing, redness and discomfort. Prolonged exposure may cause

chronic effects.

Indication of immediate medical attention and special

treatment needed

General information

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved and take precautions to protect

themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing

before reuse. Avoid contact with eyes and skin. Keep out of reach of children.

5. Fire Fighting Measures

Suitable extinguishing media Unsuitable extinguishing

Alcohol resistant foam. Dry chemical powder.

Do not use water jet as an extinguisher, as this will spread the fire.

chemical

Specific hazards arising from the source of ignition and flash back. During fire, gases hazardous to health may be formed.

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special protective equipment and precautions for firefighters Fire-fighting

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

equipment/instructions

media

Use standard firefighting procedures and consider the hazards of other involved materials.

Specific methods General fire hazards

Highly flammable liquid and vapor.

Hazardous combustion products

May include and are not limited to: Oxides of carbon. Oxides of nitrogen. chromium oxides

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Keep people away from and upwind of spill/leak. Keep unnecessary personnel away. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials containment and cleaning up for Stop leak if you can do so without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Never return spills to original containers for re-use. Clean surface thoroughly to remove residual contamination. Following product recovery, flush area with water. Prevent entry into waterways, sewers, basements or confined areas. For waste disposal, see section 13 of the SDS.

Environmental precautions

Do not discharge into lakes, streams, ponds or public waters.

7. Handling and Storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight.

Take precautionary measures against static discharges. Use non-sparking tools and explosionproof equipment. All equipment used when handling the product must be grounded. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Do not breathe mist or vapor. Do not taste or swallow.

Avoid contact with eyes, skin, and clothing.

When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product.

Avoid prolonged exposure.

Wear appropriate personal protective equipment. Should

be handled in closed systems, if possible.

Wash thoroughly after handling.

Use good industrial hygiene practices in handling this material.

When using do not eat or drink.

Conditions for safe storage, Store locked up. including any incompatibilities

Keep away from heat, sparks and open flame.

Prevent electrostatic charge build-up by using common bonding and grounding techniques.

Store in a cool, dry place out of direct sunlight.

Store in original tightly closed container.

Store in a well-ventilated place.

Store away from incompatible materials (see Section 10 of the SDS).

Keep out of reach of children.

8. Exposure Controls/Personal Protection

Occupational exposure limits

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Value Components Type 4-Heptanone, 2,6-dimethyl-TWA 145 mg/m3

(CAS 108-83-8)

25 ppm

Amines, C10-14-branched And Linear Alkyl, Bis[2,4-dihydro-4-[(2-	TWA	0.5 mg/m3
hydrox y-5- nitrophenyl)azo]-5-meth yl- 2-phenyl-3h-pyrazol-3-on		
ato(2-)]chromate(1-) (1:1)		
(CAS 84961-40-0) Methanol (CAS 67-56-1)	STEL	328 mg/m3 250 ppm
	TWA	262 mg/m3 200 ppm
Canada. British Columbia OELs. (Occu Chemical		Substances, Occupational Health and
Safety Regulation 296/97, as amended		Value
Components 4-Heptanone, 2,6-dimethyl-	Type TWA	25 ppm
(CAS 108-83-8) Methanol (CAS 67-56-1)	STEL	250 ppm
Methanol (CAS 67-56-1)	TWA	200 ppm
Canada. Manitoba OELs (Reg. 217/200 Components	ธ, । ne Workplace Safety And Hea	lth Act) Type Value
4-Heptanone, 2,6-dimethyl- (CAS 108-83-8)	TWA	25 ppm
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm
Canada. Ontario OELs. (Control of Exp	osure to Biological or Chemical A	agents)
Components	Туре	Value
4-Heptanone, 2,6-dimethyl- (CAS 108-83-8)	TWA	25 ppm
	TWA STEL	25 ppm 250 ppm
(CAS 108-83-8)		
(CAS 108-83-8) Methanol (CAS 67-56-1) Canada. Quebec OELs. (Ministry of La	STEL TWA bor - Regulation Respecting the G	250 ppm 200 ppm Qualityof the Work Environment)
(CAS 108-83-8) Methanol (CAS 67-56-1) Canada. Quebec OELs. (Ministry of La Components	STEL TWA bor - Regulation Respecting the C Type	250 ppm 200 ppm Qualityof the Work Environment) Value
(CAS 108-83-8) Methanol (CAS 67-56-1) Canada. Quebec OELs. (Ministry of La	STEL TWA bor - Regulation Respecting the G	250 ppm 200 ppm Qualityof the Work Environment) Value 145 mg/m3
(CAS 108-83-8) Methanol (CAS 67-56-1) Canada. Quebec OELs. (Ministry of La Components 4-Heptanone, 2,6-dimethyl-(CAS 108-83-8)	STEL TWA bor - Regulation Respecting the C Type TWA	250 ppm 200 ppm Qualityof the Work Environment) Value 145 mg/m3 25 ppm
(CAS 108-83-8) Methanol (CAS 67-56-1) Canada. Quebec OELs. (Ministry of La Components 4-Heptanone, 2,6-dimethyl-	STEL TWA bor - Regulation Respecting the C Type	250 ppm 200 ppm Qualityof the Work Environment) Value 145 mg/m3 25 ppm 328 mg/m3
(CAS 108-83-8) Methanol (CAS 67-56-1) Canada. Quebec OELs. (Ministry of La Components 4-Heptanone, 2,6-dimethyl-(CAS 108-83-8)	STEL TWA bor - Regulation Respecting the G Type TWA STEL	250 ppm 200 ppm Quality of the Work Environment) Value 145 mg/m3 25 ppm 328 mg/m3 250 ppm
(CAS 108-83-8) Methanol (CAS 67-56-1) Canada. Quebec OELs. (Ministry of La Components 4-Heptanone, 2,6-dimethyl-(CAS 108-83-8)	STEL TWA bor - Regulation Respecting the C Type TWA	250 ppm 200 ppm Qualityof the Work Environment) Value 145 mg/m3 25 ppm 328 mg/m3
(CAS 108-83-8) Methanol (CAS 67-56-1) Canada. Quebec OELs. (Ministry of La Components 4-Heptanone, 2,6-dimethyl-(CAS 108-83-8) Methanol (CAS 67-56-1) US. OSHA Table Z-1 Limits for Air	STEL TWA bor - Regulation Respecting the G Type TWA STEL TWA nants (29 CFR 1910.1000)	250 ppm 200 ppm Quality of the Work Environment) Value 145 mg/m3 25 ppm 328 mg/m3 250 ppm 262 mg/m3
(CAS 108-83-8) Methanol (CAS 67-56-1) Canada. Quebec OELs. (Ministry of La Components 4-Heptanone, 2,6-dimethyl-(CAS 108-83-8) Methanol (CAS 67-56-1)	STEL TWA bor - Regulation Respecting the G Type TWA STEL TWA	250 ppm 200 ppm Quality of the Work Environment) Value 145 mg/m3 25 ppm 328 mg/m3 250 ppm 262 mg/m3
(CAS 108-83-8) Methanol (CAS 67-56-1) Canada. Quebec OELs. (Ministry of La Components 4-Heptanone, 2,6-dimethyl-(CAS 108-83-8) Methanol (CAS 67-56-1) US. OSHA Table Z-1 Limits for Air Contami Components 4-Heptanone, 2,6-dimethyl-	STEL TWA bor - Regulation Respecting the G Type TWA STEL TWA nants (29 CFR 1910.1000)	250 ppm 200 ppm Quality of the Work Environment) Value 145 mg/m3 25 ppm 328 mg/m3 250 ppm 262 mg/m3 200 ppm
(CAS 108-83-8) Methanol (CAS 67-56-1) Canada. Quebec OELs. (Ministry of La Components 4-Heptanone, 2,6-dimethyl-(CAS 108-83-8) Methanol (CAS 67-56-1) US. OSHA Table Z-1 Limits for Air Contami Components	STEL TWA bor - Regulation Respecting the G Type TWA STEL TWA nants (29 CFR 1910.1000) Type	250 ppm 200 ppm Quality of the Work Environment) Value 145 mg/m3 25 ppm 328 mg/m3 250 ppm 262 mg/m3 200 ppm
(CAS 108-83-8) Methanol (CAS 67-56-1) Canada. Quebec OELs. (Ministry of La Components 4-Heptanone, 2,6-dimethyl-(CAS 108-83-8) Methanol (CAS 67-56-1) US. OSHA Table Z-1 Limits for Air Contami Components 4-Heptanone, 2,6-dimethyl-	STEL TWA bor - Regulation Respecting the G Type TWA STEL TWA nants (29 CFR 1910.1000) Type	250 ppm 200 ppm Quality of the Work Environment) Value 145 mg/m3 25 ppm 328 mg/m3 250 ppm 262 mg/m3 200 ppm Value 290 mg/m3
(CAS 108-83-8) Methanol (CAS 67-56-1) Canada. Quebec OELs. (Ministry of La Components 4-Heptanone, 2,6-dimethyl-(CAS 108-83-8) Methanol (CAS 67-56-1) US. OSHA Table Z-1 Limits for Air Contami Components 4-Heptanone, 2,6-dimethyl-(CAS 108-83-8) Methanol (CAS 67-56-1) US. ACGIH Threshold Limit Values	STEL TWA bor - Regulation Respecting the G Type TWA STEL TWA nants (29 CFR 1910.1000) Type PEL PEL	250 ppm 200 ppm 200 ppm 2ualityof the Work Environment) Value 145 mg/m3 25 ppm 328 mg/m3 250 ppm 262 mg/m3 200 ppm Value 290 mg/m3 50 ppm 260 mg/m3 200 ppm
(CAS 108-83-8) Methanol (CAS 67-56-1) Canada. Quebec OELs. (Ministry of La Components 4-Heptanone, 2,6-dimethyl- (CAS 108-83-8) Methanol (CAS 67-56-1) US. OSHA Table Z-1 Limits for Air Contami Components 4-Heptanone, 2,6-dimethyl- (CAS 108-83-8) Methanol (CAS 67-56-1) US. ACGIH Threshold Limit Values Components	STEL TWA bor - Regulation Respecting the G Type TWA STEL TWA nants (29 CFR 1910.1000) Type PEL PEL Type	250 ppm 200 ppm 201 ppm 202 ppm 203 ppm 145 mg/m3 25 ppm 328 mg/m3 250 ppm 262 mg/m3 200 ppm Value 290 mg/m3 50 ppm 260 mg/m3 200 ppm Value Value Value Value Value Value Value
(CAS 108-83-8) Methanol (CAS 67-56-1) Canada. Quebec OELs. (Ministry of La Components 4-Heptanone, 2,6-dimethyl-(CAS 108-83-8) Methanol (CAS 67-56-1) US. OSHA Table Z-1 Limits for Air Contami Components 4-Heptanone, 2,6-dimethyl-(CAS 108-83-8) Methanol (CAS 67-56-1) US. ACGIH Threshold Limit Values Components 4-Heptanone, 2,6-dimethyl-(CAS 108-83-8)	STEL TWA bor - Regulation Respecting the G Type TWA STEL TWA nants (29 CFR 1910.1000) Type PEL PEL Type TWA	250 ppm 200 ppm 2ualityof the Work Environment) Value 145 mg/m3 25 ppm 328 mg/m3 250 ppm 262 mg/m3 200 ppm Value 290 mg/m3 50 ppm 260 mg/m3 200 ppm Value 25 ppm
(CAS 108-83-8) Methanol (CAS 67-56-1) Canada. Quebec OELs. (Ministry of La Components 4-Heptanone, 2,6-dimethyl-(CAS 108-83-8) Methanol (CAS 67-56-1) US. OSHA Table Z-1 Limits for Air Contami Components 4-Heptanone, 2,6-dimethyl-(CAS 108-83-8) Methanol (CAS 67-56-1) US. ACGIH Threshold Limit Values Components 4-Heptanone, 2,6-dimethyl-	STEL TWA bor - Regulation Respecting the G Type TWA STEL TWA nants (29 CFR 1910.1000) Type PEL PEL Type	250 ppm 200 ppm 201 ppm 202 ppm 203 ppm 145 mg/m3 25 ppm 328 mg/m3 250 ppm 262 mg/m3 200 ppm Value 290 mg/m3 50 ppm 260 mg/m3 200 ppm Value Value Value Value Value Value Value

#28042 Page: 4 of 14 Issue date 09-July-2018

Components	Туре	Value	
4-Heptanone, 2,6-dimethyl- (CAS 108-83-8)	TWA	150 mg/m3	
,		25 ppm	
Methanol (CAS 67-56-1)	STEL	325 mg/m3	
		250 ppm	
	TWA	260 mg/m3	
		200 ppm	

Biological limit values

ACGIH Biological Exposure Indices Components		Value	Determinant	Specimen Sampling Time
Methanol (CAS 67-56-1)	15 mg/L	Methanol	Urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines See above

Canada - Alberta OELs: Skin designation

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

Canada - Manitoba OELs: Skin designation

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

Canada - Ontario OELs: Skin designation

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

Canada - Quebec OELs: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

US. NIOSH: Pocket Guide to Chemical Hazards Methanol

(CAS 67-56-1)

Appropriate engineering Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates controls should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Impervious gloves. Confirm with reputable supplier first.

Other As required by employer code.

Respiratory protection Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.

Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134).

Can be absorbed through the skin.

CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

Thermal hazards Not applicable.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace. When using do not eat or drink.

9. Physical and Chemical Properties

Appearance Liquid Physical state Liquid. Liquid. **Form** Color Colored Mild Odor

Odor threshold Not available. Not available. pН < 32 °F (< 0 °C) Melting point/freezing point

Initial boiling point and boiling

range

147.2 - 338 °F (64 - 170 °C)

Not available. Pour point

0.79 Specific gravity

Not available. Partition coefficient

(n-octanol/water)

Flash point 51.8 °F (11.0 °C) Tag Closed Cup **Evaporation rate** Faster than n-Buthyl Acetate

Flammability (solid, gas) Not applicable. Upper/lower flammability or sive limits expl 6 %

Flammability limit - lower

(%)

36 % Flammability limit - upper

(%)

Not available. Explosive limit - lower (%)

Not available. Explosive limit - upper (%) 96 mm Hg @ 20°C Vapor pressure Vapor density Lighter than air Not available. Relative density

Slight Solubility(ies)

Auto-ignition temperature Not available. Not available. **Decomposition temperature Viscosity** Not available.

Other information

Explosive properties Not explosive. Oxidizing properties Not oxidizing. VOC (Weight %) 788 g/l

10. Stability and Reactivity

Reactivity

Possibility of hazardous

reactions

This product may react with strong acids and strong oxidizing agents.

Hazardous polymerization does not occur.

Chemical stability Material is stable under normal conditions.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.

Do not mix with other chemicals.

Hazardous decomposition

Incompatible materials

products

Strong oxidizing agents. Strong acids and strong bases. Amines. Aluminum. May include and are not limited to: Oxides of carbon. Oxides of nitrogen.

11. Toxicological Information

Routes of exposure Eye, Skin contact, Inhalation, Ingestion. Information on

likely routes of exposure

Ingestion Toxic if swallowed. May cause stomach distress, nausea or vomiting.

Inhalation Toxic if inhaled. May cause damage to organs by inhalation. May cause damage to organs

through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness.

Headache. Nausea, vomiting.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

Symptoms related to physical, chemical and

 $\begin{tabular}{ll} \textbf{the}\\ \textbf{May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes.} \end{tabular}$

Exposed individuals may experience eye tearing, redness and discomfort.

toxicological characteristics

Information on toxicological effects

Acute toxicity Toxic if inhaled. Toxic if swallowed. Narcotic effects.

Components 4-Heptanone, 2,6-dimethyl- (CAS 108)	Species 3-83-8)	Test Results
Acute Dermal	,	
LD50		16000 mg/kg
		4556 mg/kg, 24 Hours
	Rabbit	> 12172 mg/kg, 2 wk
Inhalation	Rat	> 2000 mg/kg, 24 Hours
LC50	Nat	> 10 drops, 2 wk
		> 14.5 mg/L, 4 Hours
	Guinea pig	> 14.5 mg/L, 4 Hours
<i>Oral</i> LD50	Rat	2300 mg/l/4h
		2300 ppm
		100 % (saturated), 6 Hours
	Mouse	1416 mg/kg
	Rat	> 2000 mg/kg 5750 mg/kg

#28042 Page: 7 of 14 Issue date 09-July-2018

Components **Species Test Results**

Amines, C10-14-branched And Linear Alkyl,

Bis[2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl-2-phenyl-3h-pyrazol-3-onato(2-)]chromate(1-) (1:1) (CAS 84961-40-0)

Acute

Dermal

LD50 Not available

Inhalation

Not available

LC50

Rat Oral

LD50

1400 mg/kg, BASF Methanol (CAS 67-56-1)

Acute

Rabbit

Dermal

Rat LD50

15800 - 20000 mg/kg, SIDS report/HSDB

Inhalation > 450000 mg/kg, SIDS report/HSDB

LC50 Cat 85.4 mg/l/4h, HSDB

85.4 mg/L, 4.5 Hours, ECHA/HSDB

43.7 mg/L, 6 Hours, ECHA

Mouse 79.4 mg/L, 134 Minutes, ECHA

Rat > 115.9 mg/L, 4 Hours, ECHA

64000 ppm, 4 Hours, HSDB

130.7 mg/L, 4 Hours, ECHA

128.2 mg/L, 4 Hours, ECHA

92.6 mg/L, 6 Hours, ECHA

87.5 mg/L, 6 Hours, ECHA

83.2 - 128.8 mg/l/4h, SIDS report/HSDB

Oral

LD50 Dog 82.1 mg/L, 6 Hours, ECHA

8000 mg/kg, HSDB

143 - 300 mg/kg, HSNO Human

CCID/Sigma-Aldrich

Monkey 7000 - 9000 mg/kg, ECHA

6000 mg/kg, ECHA

3000 mg/kg, RTECS

Mouse

Pig

2000 mg/kg, HSDB

Rabbit 7300 mg/kg, HSDB

Rat > 5000 mg/kg, ECHA

14200 - 14400 mg/kg, RTECS

14.4 g/kg, HSDB

1187 - 2769 mg/kg

790 - 13000 mg/kg, SIDS report/HSDB

5628 mg/kg, HSDB

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Exposure minutesNot available.Erythema valueNot available.Oedema valueNot available.

Serious eye damage/eye

irritation

Causes eye irritation.

Corneal opacity valueNot available.Iris lesion valueNot available.Conjunctival reddeningNot available.

value

Conjunctival oedema value Not available.

Recover days Not available.

Respiratory or skin sensitization

Canada - Alberta OELs: Irritant

4-Heptanone, 2,6-dimethyl- (CAS 108-83-8) Irritant Amines, C10-14-

branched And Linear Alkyl, Irritant

Bis[2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl

-2-phenyl-3h-pyrazol-3-onato(2-)]chromate(1-) (1:1) (CAS 84961-40-

0)

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Mutagenicity Non-hazardous by WHMIS/OSHA criteria.

Carcinogenicity See below.

IARC Monographs. Overall Evaluation of Carcinogenicity

Amines, C10-14-branched And Linear Alkyl, Volume 49 - 3 Not classifiable as to carcinogenicity to humans.

Bis[2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl

-2-phenyl-3h-pyrazol-3-onato(2-)]chromate(1-) (1:1) (CAS 84961-40-

0)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed. Specific target organ toxicity - single exposure

Reproductive toxicity Specific target organ toxicity - repeated exposure Aspiration hazard

Teratogenicity Chronic effects

produce significant maternal toxicity. Causes damage to organs. May cause drowsiness and

Ecotoxicity See below

Ecotoxicological data

Components Species Test Results

Methanol (CAS 67-56-1) EC50 Water flea (Daphnia magna) > 10000 mg/L, 48 hours

Aquatic

Crustacea LC50 Fathead minnow (Pimephales promelas) > 100 mg/L, 96 hours

Fish No data is available on the degradability of this product.

Persistence and degradability Bioaccumulative potential

Mobility in soil

Mobility in general

No data available.

Not available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone

creation i I di i I b l i i I) d f

hi

13. Disposal Considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

product residues. This material and its container must be disposed of in a safe manner (s

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

May damage fertility or the

unborn child.

dizziness.

Contains a potential teratogen. Methanol has produced teratogenic effects

produced teratogenic effects in mice exposed by

inhalation to high concentrations that did not

Not available.

Not an aspiration hazard.

Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may

be harmful.

14. Transport Information

Transport of Dangerous Goods (TDG) Proof of Classification

Classification Method: Classified as per Part 2, Sections 2.1 - 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.

U.S. Department of Transportation (DOT) Basic

shipping requirements:

UN number UN1992

Proper shipping name Flammable liquids, toxic, n.o.s.

Technical name Methanol

Hazard class 3

Subsidiary hazard class 6.1(PGI, II)

Packing group

Special provisions IB2, T7, TP2, TP13

Packaging exceptions 150
Packaging non bulk 202
Packaging bulk 243

Transportation of Dangerous Goods (TDG - Canada) Basic

shipping requirements:

UN1992 **UN** number

Proper shipping name FLAMMABLE LIQUID, TOXIC, N.O.S.

Technical name Methanol Hazard class 3 Subsidiary hazard class 6.1 Packing group Ш Special provisions 16

DOT



15.Regulatory Information

Canadian federal regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Methanol (CAS 67-56-1)

1 TONNES

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations Not

regulated.

WHMIS 2015 Exemptions

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, $29\ CFR\ 1910.1200$. **US** federal regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) Not

regulated.

Bis[2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl -2-phenyl-3h-pyrazol-3-onato(2-)]chromate(1-) (1:1) (CAS 84961-40-0) Methanol (CAS 67-56-1) US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not listed. Superfund Amendments and Reauthorization Act of 1986 (SARA) Hazard categories Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No No SARA 302 Extremely hazardous substance SARA 311/312 Hazardous chemical No SARA 313 (TRI reporting) Chemical name CAS by numberwt. 84961- 1-5* 40-0 Amines, C10-14-branched And Linear Alkyl, Bis[2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-meth yl-2-phenyl-3h-pyrazol-3-onato(2-80-)]chromate(1-) (1:1) Methanol 67-56-1 100* Other federal regulations Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Amines, C10-14-branched And Linear Alkyl, Bis[2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl-2-phenyl-3h-pyrazol-3-onato(2-)]chromate(1-) (1:1) (CAS 84961-40-0) Methanol (CAS 67-56-1) Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Not regulated. **US** state regulations See below US - California Hazardous Substances (Director's): Listed substance 4-Heptanone, 2,6-dimethyl- (CAS 108-83-8) Amines, C10-14-branched And Linear Alkyl, Listed. Bis[2,4-dihydro-4-[(2-hydroxy-5nitrophenyl)azo]-5-m ethyl-2-phenyl-3h-pyrazol-3-onato(2-)]chromate(1-) (1:1) (CAS 84961-40-0) Methanol (CAS 67-56-1) Listed. US - Illinois Chemical Safety Act: Listed substance Amines, C10-14-branched And Linear Alkyl, Bis[2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl-2-phenyl-3h-pyrazol-3-onato(2-)]chromate(1-) (1:1) (CAS 84961-40-0) Methanol (CAS 67-56-1) US - Louisiana Spill Reporting: Listed substance Amines, C10-14-branched And Linear Alkyl. Listed. Bis[2,4-dihydro-4-[(2-hydroxy-5nitrophenyl)azo]-5-m ethyl-2-phenyl-3h-pyrazol-3-onato(2-)]chromate(1-) (1:1) (CAS 84961-40-0) Methanol (CAS 67-56-1) Listed. US - Michigan Critical Materials Register: Parameter number Amines, C10-14-branched And Linear Alkvl. CHROMIUM Bis[2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-m ethyl-2-phenyl-3h-pyrazol-3-onato(2-)]chromate(1-) (1:1) (CAS 84961-40-0) US - Minnesota Haz Subs: Listed substance 4-Heptanone, 2,6-dimethyl- (CAS 108-83-8) Listed. Amines, C10-14-branched And Linear Alkyl, Listed. Bis[2,4-dihydro-4-[(2-hydroxy-5nitrophenyl)azo]-5-m ethyl-2-phenyl-3h-pyrazol-3-onato(2-)]chromate(1-) (1:1) (CAS 84961-40-0) Methanol (CAS 67-56-1) Listed. US - New Jersey RTK - Substances: Listed substance 4-Heptanone, 2,6-dimethyl- (CAS 108-83-8) Methanol (CAS 67-56-1)

Listed.

CERCLA Hazardous Substance List (40 CFR 302.4)
Amines, C10-14-branched And Linear Alkyl,

US - Pennsylvania RTK - Hazardous Substances: Special hazard

Amines, C10-14-branched And Linear Alkyl,

Bis[2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl-2-phenyl-3h-pyrazol-3-onato(2-)]chromate(1-) (1:1) (CAS 84961-40-0)

US - Texas Effects Screening Levels: Listed substance

4-Heptanone, 2,6-dimethyl- (CAS 108-83-8) Listed. Amines, C10-14-branched And Linear Alkyl, Listed. Bis[2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-m ethyl-2-phenyl-

3h-pyrazol-3-onato(2-)]chromate(1-) (1:1) (CAS 84961-40-0)

Methanol (CAS 67-56-1) Lis

US. Massachusetts RTK - Substance List

4-Heptanone, 2,6-dimethyl- (CAS 108-83-8)

Methanol (CAS 67-56-1)

US. New Jersey Worker and Community Right-to-Know Act

Amines, C10-14-branched And Linear Alkyl,

Bis[2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl-2-phenyl-3h-pyrazol-3-onato(2-)]chromate(1-) (1:1)

(CAS 84961-40-0)

Methanol (CAS 67-56-1)

US. Pennsylvania Worker and Community Right-to-Know Law

4-Heptanone, 2,6-dimethyl- (CAS 108-83-8)

Amines, C10-14-branched And Linear Alkyl,

Bis[2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl-2-phenyl-3h-pyrazol-3-onato(2-)]chromate(1-) (1:1) (CAS 84961-40-0)

Methanol (CAS 67-56-1)

US. Rhode Island RTK

4-Heptanone, 2,6-dimethyl- (CAS 108-83-8)

Amines, C10-14-branched And Linear Alkyl,

Bis[2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl-2-phenyl-3h-pyrazol-3-onato(2-)]chromate(1-) (1:1)

(CAS 84961-40-0)

Methanol (CAS 67-56-1)

US. California Proposition 65

WARNING: This product can expose you to Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Methanol (CAS 67-56-1) Listed: March 16, 2012

Inventory status

Country(s) or region	Inventory name	On	inventory
Canada	Domestic Substances List (DSL)	(yes/no)*	
Canada	Non-Domestic Substances List (NDSL)		Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory		No
	, ,		Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16.Other Information









The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date 09-July-2018

Version # 02

Effective date 15-May-2017

Prepared by Dell Tech Laboratories Ltd. Phone: (519) 858-5021

Other information For an updated SDS, please contact the supplier/manufacturer listed on the first page of

the document.

#28042 Page: 14 of 14 Issue date 09-July-2018