



WHITE DRY GLAZE
SERIES 507-100
WHITE

DESCRIPTION: 507-100 is a white dry glaze to create very nice effects.

PRODUCT DATA:

PRODUCT CODE: 507-100
SOLID % by Vol: 12 ± 1%
SOLID % by WT: 28 ± 1%
VOC: 764.2 g/L
DENSITY: 1.058 Kg/L
SHELF LIFE: 12 months

MIXING RATIO:

READY TO USE.
MIX WELL BEFORE USING.

DRYING TIMES:

READY TO WORK: 15-20 minutes

Note: Drying times may vary depending on thickness applied, temperature and/or humidity.

Warning: Total film thickness of the finish should not exceed 5 mils dry film.

APPLICATION:

Surfaces should be clean, dry and free of all traces of grease or oil. Ensure product is stirred thoroughly mixed according to specification before applying. Avoid thick coats. Remove most of the glaze with a "Scotch Brite" or a cloth which has been soaked in solvent.

APPLICATION EQUIPMENT:

SPRAY GUN
PRESSURE TANK
AIR MIX
AIRLESS

STORAGE:

Store in a dry and cool area. Close the container properly after use.

The customer is responsible for following the recommended application procedures. Failure to adhere to these specifications may result in poor appearance or failure of film. This product is for professional use only. Consult your local representative before applying with other manufacturer products. The customer should test the complete system for adhesion, compatibility and performance prior to full scale application. Please refer to the Safety Data Sheet (SDS) for safety information and precautions prior to using this product. We ONLY guarantee our product to conform to our quality. Our responsibility as manufacturer is limited to the cost of the product. Please feel free to contact us at (819) 367-2201 for any further inquiries regarding this product. All information on this product data sheet is subject to change without notice.